

# High Speed Midrange Harrow



**New from Rite Way**

# High Speed Midrange Harrow

Go faster and cover more field with less footage - and better results!  
Transporting your equipment is easy and manoeuvring it effortless.

Rite Way introduces the new patent-pending High Speed Harrow, which allows you to increase your field speed by 50% or more. This means greater productivity and time savings during the critical seasonal rush.

The High Speed Harrow will do an even better job of managing your straw, because the faster you go, the more the harrow will shatter and spread the straw. The High Speed Harrow can also be used prior to seeding to work your field and control weeds, and can be used to effectively incorporate seed or chemicals. You will find our compact design easier to transport, and easier to manoeuvre around power poles and other obstacles.

## HOW DO WE DO IT?

Rite Way developed this innovative harrow by incorporating our patent-pending, two-stage shock isolation system:

On the main frame - air bag suspension, the same as that used on high-end commercial vehicles

On the wings - walking beam axles

On the harrow sections - parallel linkage with coil spring down pressure



## OTHER FEATURES

Hydraulic tine angle adjustment - a standard feature

Patented FORWARD™ unfolding system

Two different models: 55' and 78'

### Tines

1/2" x 22" tines



P.O. Box 26097  
Regina, SK Canada S4R 8R7  
www.ritewaymfg.com  
info@ritewaymfg.com  
306-337-4440  
1-800-352-8822

## SPECIFICATIONS

Working Width	55' / 16.8 m	77' / 23.5 m
Transport Length	48' / 14.6 m	54' 6" / 16.7 m
Transport Height	11' 6" / 3.5 m	11' 6" / 3.5 m
Weight	9,400 lbs / 4 263 kg	10,600 lbs / 4 808 kg
Tines	1/2" x 22" (1.3 x 55.9 cm)	
Tine Angle Control	50° - 90° hydraulic control option	
Harrow Sections	11' (3.3 m) wide, 5 bar sections	
Wing and centre frame tubing	8" x 8 x 0.25" (20 x 20 x .63 cm)	
Harrow suspension	Parallel linkage	
Field/Transport Fold/Unfold	Patented <b>FORWARD™</b> system	
Tires, main frame	12.5L - 15	
Tires, wings	12.5L - 15	
Hydraulic outlets required	3	
Safety chain, SMV sign & lights	Standard	
Horsepower Requirements	3-5 hp/ft	

Because we are constantly striving to improve our products, we reserve the right to change the design, materials and specifications without notice. Illustrations may include optional equipment and may not include all standard equipment.

Printed in Canada 1410